

SAL-1450-2

NEW

SUPER Power High Pressure Washer with Sequencer Control

Example Of Use with SUPER High Pressure

- < Cleaning >
- Asphalt pavement
 - Crawlers of Crane
 - Stains (Paint preparation)
 - Ship's bottoms and Piers under water
 - Deburring

Stop Device for abnormal High water temperature

Overload Stop Device

Emergency Stop Button

Stop Devices for Safety

Stop Device for dry run

Anti-freezing Heater

Prevention for pump wear

Hourmeter

Oil lamp

Easy check for maintenance Schedule

Boiler Unit SHB-500

Specification	
Product Name	SHB-500
Code Number	[50Hz] 03B0009 · [60Hz] 03B010
Max Pressure (kgf/cm ²)	50.0 (5.10)
Fuel Tank Capacity (L)	8.5 ~ 15.0
Voltage (V)	100
Fuel	Light Fuel (white kerosene is OK)
Fuel Tank Capacity (L)	20
Temperature	30 ~ 70°C
Dimensions (LxWxH) (mm)	1110x750x996
Weight (kg)	170.0

Std Equipment
High Pressure Hose | 3/8" 10m x 1-3/8" 2m x 1 (With special connectors)

Using with cold water high pressure washer



※Same Body as SAL-2 type



Specification	15kW/20.0PS	
Product Name	SAL-1450-2	
Code Number	[50Hz] 03B451 · [60Hz] 03B551	
PUMP	Max Pressure (kgf/cm ²)	49.0 (500)
	Flow Rate (L/min)	14.0
	RPM	1290
MOTOR	Power Rating	[50Hz] 15kW/1465min ⁻¹ (4P) [60Hz] 15kW/1760min ⁻¹ (4P)
	Rated Voltage (V)	Power Circuit: 200/Operating Circuit: 200
	Rated Current (A)	[50Hz] 58 (Insulation Class: B) · [60Hz] 54 (Insulation Class: B)
STARTER	Starting Method	Star-Delta Starting
	Cable	14mm ² x 4C x 1.0m
Dimensions (LxWxH) (mm)	1185x710x940	
Weight (kg)	355	

※SAL-1450-2 is for direct water connection

Equipment	Trigger gun + Spray Lance 1050mm
	Straight Angle Nozzle
	High Pressure Hose 20m
	Power Cable 10m
	Water Supply Hose Set 10m
	Face Shield
	Nitrile Gloves

Option	
Connector	Coupler 1/2"

High Pressure Power washer

SUPERACE[®]
WASHER

SUPER INDUSTRIES CO., LTD

<http://www.super-ace.co.jp/english/>