

SUPERACE® WASHER**SEL-SS_{type}**

The industry's
first compact,
light weight
diesel model

The industry's first Diesel Compact High Pressure Washer

Compact

Can be easily loaded on Truck

Diesel Engine

Excellent Durability and Superior Safety

Non-Stop Operation

25L large fuel tank installed, Max 8 hours non-stop operation

Lineup

Big flow 30L/min with 20Mpa, can be used for many application

Single Point Hook for lift



Auto Stop device for Dry Run

Large opening Panel for maintenance



Small and Light



Specification		Large Amount of Water	HIGH pressure
Product Name		SEL-3010SS	SEL-1620SS
Code Number		039790	039794
PUMP	Max Pressure(kgf/cm ²)	10.0(102)	20.0(204)
	Flow Rate(L/min)	30.0	16.0
	RPM	1750	
ENGINE	Type	Water-cooled 4-cycle diesel engine	
	Total displacement (cc)	479	
	Power Rating	7.4kW(10.0PS)/2800min ⁻¹	
	Max Power Rating	9.3kW(12.7PS)/3600min ⁻¹	
	Starting Method	Cell Starter	
	Fuel Type	JIS No.2 light oil (Diesel)	
	Tank size (L)	25	
Dimensions (LxWxH)(mm)		922x700x850	
Weight(kg)		198.0	

Recommendation

Piping tester T-85

Code no. 03T446

Test for water leakage
of the pipe Max Flow
Rate: 38.0L/min
Max Pressure: 15.0MPa



型式名	SEL-3010SS	SEL-1620SS
Equipment	Trigger gun + Spray Lance	
	Straight Nozzle	
	High Pressure Hose 20m	
	Suction Hose 3m	
	Strainer Filter	
	Bypass Hose 3m	



High Pressure Power washer

SUPERACE®
WASHER

SUPER INDUSTRIES CO.,LTD

<http://www.super-ace.co.jp/english/>