

洗浄機機種別噴口表

- 各ノズルを装着する場合、機種毎に適したノズルを選定する必要がありますので、下記表をご確認下さい。
- 各商品コード及び詳細については、各種オプションパーツをご覧ください。
- 記載の無い商品機種の適合については、最寄りの当社営業店または販売店にご相談下さい。

型 式		能 力		可変ノズル	真鍮製可変ノズル	トルネードノズル	逆噴射ノズル	ノズルチップ(直射)		サンドブラスト
タイプ	型 番	水量 (L/min)	圧力 (Mpa)	φ	φ	φ	#	#	φ	
										
SEC-2N	1310	13.0	10.0	1.3	1.4	1.3	084	1/8	56	1.4
	1315	13.0	15.0	1.2	1.3	1.2	074	1/8	49	1.2
	3007	29.0	7.0	2.0	2.5	1.7	125	1/8	161	2.1
	1520	15.0	20.0	1.1	1.3	1.2	074	1/8	49	1.1
	1616	16.0	16.0	1.3	1.4	1.3	084	1/8	62	1.3
	1012	10.0	12.0	1.1	1.3	1.1	074	1/8	49	1.1
	1015	10.0	15.0	1.0	1.2	1.0	073	1/8	31	—
	1020	10.0	20.0	1.0	1.2	1.0	073	1/8	31	—
SER-5	2308	23.0	8.0	1.8	2.0	1.7	105	1/8	111	2.1
	2010	20.0	10.0	1.7	1.7	1.7	095	1/8	93	2.1
	3007	29.0	7.0	2.0	2.5	1.7	125	1/8	161	2.1
	1315	13.0	15.0	1.2	1.3	1.2	074	1/8	49	1.2
	1616	16.0	16.0	1.3	1.4	1.3	084	1/8	62	1.3
	1620	16.0	20.0	1.1	1.3	1.1	073	1/8	49	1.1
	2015	20.0	15.0	1.5	1.7	1.5	085	1/8	80	1.5
	3010	29.0	10.0	2.0	2.2	1.7	106	1/8	136	2.1
SER	1450-2	15.0	50.0	—	—	025 (50MPa)	—	1/4	1.2Sa	—
	1230i	12.0	30.0	—	1.1	025 (35MPa)	073 (35MPa)	1/8	31	超硬#31
	6005-3	60.0	4.9	2.9	2.7	—	※商品ページに掲載	1/4	297	2.1
SE-ST6	2107	21.0	7.0	1.8	2.0	1.7	105	1/8	111	2.1
	3005	27.0	5.0	2.4	2.6	1.7	126	1/8	173	2.1
SEK-SSV	2008	22.3	8.0	2.0	2.0	1.7	106	1/8	111	2.1
	1315	13.0	15.0	1.2	1.3	1.2	074	1/8	49	1.2
SEV-SS SEV-SSP	2108	23.0	8.0	1.8	2.0	1.7	105	1/8	111	2.1
	1615	15.0	15.0	1.2	1.3	1.2	075	1/8	56	1.3
	2110	20.0	10.0	1.7	1.7	1.7	095	1/8	93	2.1
	3007	29.0	7.0	2.4	2.6	1.7	106	1/8	173	2.1
	1620	16.0	20.0	1.2	1.3	1.2	074	1/8	49	1.2
	2015	20.0	15.0	1.5	1.7	1.5	085	1/8	80	1.5
	3010	30.0	10.0	2.0	2.2	1.7	106	1/8	148	2.1
SEV-SSi	1230	12.0	30.0	—	1.1	025 (35MPa)	073 (35MPa)	1/8	150×0/6.1	超硬#31
SEL-SS	3010	30.0	10.0	2.0	2.2	1.7	106	1/8	148	2.1
	1620	16.0	20.0	1.2	1.3	1.2	074	1/8	49	1.2
SEL-SSN3	1835	18.0	34.3	—	1.3	035 (35MPa)	074 (35MPa)	1/8	43	超硬#43
	3617	35.5	16.7	—	2.2	1.7	※商品ページに掲載	1/8	136	2.1
	1450	14.0	49.0	—	—	025 (50MPa)	—	1/8	1.2Sa	—
SLC eGX SLR eGX	1505	15.0	5.0	1.8	2.0	1.7	095	1/8	99	1.8
SBR	1105	11.0	4.5	1.4	1.5	1.5	084	1/8	74	1.5
	0807	8.0	7.0	1.1	1.3	—	—	1/8	37	1.1

型 式		能 力		可変ノズル	真鍮製可変ノズル	トルネードノズル	逆噴射ノズル	ノズルチップ(直射)	サンドブラスト
タイプ	型 番	水量 (L/min)	圧力 (Mpa)	φ	φ	φ	#	#	φ
									
SH	0807-50	6.0	6.0	1.2ハイロー	—	—	—	1/8 37	—
	0807-60	8.0	6.0	1.2ハイロー	—	—	—	1/8 43	—
SBR	1105	11.0	4.5	1.4	1.5	1.5(060)	084	1/8 74	1.5
	0807	8.0	7.0	1.1	1.3	—	—	1/8 37	1.1
SBR-4	3005-50	24.0	5.0	2.4	2.6	1.7(070)	125	1/8 173	2.1
	3005-60	28.0	5.0	2.4	2.6	1.7(070)	116	1/8 173	2.1
	2308-50	24.0	7.8	2.0	2.0	1.7(070)	105	1/8 148	1.8
	2308-60	23.0	7.8	2.0	2.0	1.7(070)	105	1/8 148	1.8
	1315-50	12.0	14.7	1.1	1.3	1.1(033)	074	1/8 43	1.1
	1315-60	14.0	14.7	1.1	1.3	1.1(033)	074	1/8 43	1.1
SAR-N3 SAR-NS2 SAR-NS3	2308-50	24.0	8.0	2.0	2.0	1.7(070)	105	1/8 148	1.8
	2308-60	23.0	8.0	2.0	2.0	1.7(070)	105	1/8 124	1.8
	3005	30.0	5.0	2.9	2.7	1.7(070)	126	1/4 223	2.1
	3007	28.0	7.0	2.4	2.6	1.7(070)	106	1/8 173	2.1
	1315-50	12.0	14.7	1.1	1.3	1.1(033)	074	1/8 43	1.1
	1315-60	14.0	14.7	1.1	1.3	1.1(033)	074	1/8 43	1.1
	3010-50	28.0	10.0	2.0	2.2	1.7(070)	105	1/8 136	1.8
	3010-60	28.0	10.0	2.0	2.2	1.7(070)	105	1/8 148	1.8
	1520	15.0	20.0	1.2	1.3	1.2(035)	074	1/8 49	1.2
	2015	20.0	15.0	1.5	1.7	1.5(060)	085	1/8 80	1.5
	2020	20.0	20.0	1.3	1.4	1.3(040)	084	1/8 62	1.5
	3014	28.0	14.0	2.0	2.0	1.7(070)	105	1/8 124	2.0
	1525	15.0	24.5	—	1.3	1.1(033)	074	1/8 49	—
	3018	30.0	18.0	1.9	2.0	1.7(070)	095	1/8 124	1.8
1535	15.0	35.0	—	1.2	030(35MPa)	—	1/8 37	超硬#37	
SAR-NP	2308NP-50	24.0	7.5	2.0	2.0	1.7(070)	105	1/8 124	1.8
	2308NP-60	23.0	7.5	2.0	2.0	1.7(070)	105	1/8 124	1.8
	3007NP	28.0	6.8	2.4	2.6	1.7(070)	106	1/8 173	2.1
SAL-2	1450	14.0	49.0	—	—	025(50MPa)	—	1/4 1.2Sa	—
SAL-3	1830	18.0	30.0	—	1.3	035(35MPa)	—	1/8 49	超硬#49
	2821	28.0	21.0	—	1.7	—	—	1/8 99	2.1
	2134	21.0	34.0	—	1.4	045(35MPa)	—	1/8 56	超硬#56
SHJ-S	1408	14.0	7.8	—	—	—	084	1/8 74	1.3
	1510	15.0	9.8	—	—	—	094	1/8 74	1.3
	2510	25.0	10.0	—	—	—	105	1/8 148	1.8
SAR-VN-2	1315	13.0	15.0	—	—	—	074	1/8 56	1.3
	1520	15.0	20.0	—	—	—	074	1/8 49	1.2
SAL-VNT-3	1532	15.0	32.0	—	—	—	—	1/8 0003	超硬#43
SEL-V-3	1425	14.8	24.5	—	—	—	—	1/8 37	超硬#37